U.S. Department of Agriculture AGRICULTURAL MARKETING SERVICE FEDERAL GRAIN INSPECTION SERVICE

## QUESTIONNAIRE FOR PROPOSED DIVERTER-TYPE MECHANICAL SAMPLER

Facility Name, City, State

## FORM APPROVED OMB NO. 0581-0309

According to the Paperwork Reduction Act of 1995, an agency may not conduct or sponsor, and a person is not required to respond to a collection of information unless it displays a valid OMB control number. The valid OMB control number for this information collection is 0581-0309. The time required to complete this information collection is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information.

						<u> </u>					
Field Office											
Kind of Elevator				Capacity							
Authorization - Select All that Apply											
Diverter Non-diverter Probe				All Grains Small Grains			Coarse Grains - Not Corn				
In Out		Cargo	Barç	ges		Hoppe	r Cars		Carlots		Trucks
D/T Make and Model	S/N				Spo	out	Belt		Spout / Belt Size		
General Location	Spo	out / Belt Name			Spout / Belt	Angle			Belt Speed		
Power: Air Elec		dy Dimensions			Pelican Stro	ke			Pelican Opening	LxW	
Grain Drop Before Sampler (ft)	Gra	in Drop After Sa	mpler (ft)		Access Safe	9			Inspection Door C	K?	
						•	Yes	No		Yes	No
Verified No Auxilliary Controls	Loc	cation of Lockout	OK?		Lights OK fo	or Exan	ns?				
	No	Ye		No			/es	No			
Is Pelican Movement Steady?		es Pressure Retu	-	tly?	Air Pressure	e at Res	st PSI				
	No	Ye		No							
Timer Make and Model	Gra	in Flow Rate Pas	t Sampler	•	Calculated 1	Timer S	_	.			
					D !! 0		S	econds			
Secondary Make and Model	S/N				Delivery Sys	stem avity	Dno	umatic	Grams per Sampl	е	
Total No. of Samples	Qua	antity Adjustmen	t Sealed?		Delivery & C				Excess Returned	to Lot?	
		Ye		No			Yes	No		Yes	No
<b>Dust Control Locations</b>											
Weights:											
GIPSA Class X		GIPSA Clas	ss Y		Certified	t		Other			
Number of Shipping Bins:	Dep	oth (ft)			Graded				Procedures to Sto	p Breaka	ige:
					Before	or	After R	elease			
Carrier I.D. by:	·										
Radio		Visual			Other						
Remarks/special restrictions w	nen used	I to sample offici	ally:								
Signature of Official Personnel									Date:		
FORM FGIS 998 (05/25) Previous editions are obsolete. Expires 05/28											
			,= .: 50 00/								

	nt of Agriculture	FORM APPROVED OMB NO. 0581-0309								
	ARKETING SERVICE SPECTION SERVICE	According to the Paperwork Reduction Act of 1995, an agency may								
QUESTIONNAIRE	FOR PROPOSED	not conduct or sponsor, and a person is not required to respond to a collection of information unless it displays a valid OMB control number. The valid OMB control number for this information collection is 0581-0309. The time required to complete this information collection is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data								
· ·	CHANICAL SAMPLER									
Facility Name, City, State										
1										
•		sources, gathering and maintaining and reviewing the collection of info								
		and reviewing the conection of fino	imation.							
Field Office 2		<u>,                                      </u>								
Kind of Elevator		Capacity 4								
Authorization - Select All that Apply										
Diverter Non-diverter	Probe 5	All Grains Small Grains	Coarse Grains - Not Corn							
In Out	Cargo Barges	Hopper Cars	Carlots Trucks							
D/T Make and Model 6	S/N <b>7</b>	Spout Belt 8	Spout / Belt Size							
General Location 10	Spout / Belt Name	Spout / Belt Angle 12	Belt Speed 13							
Power: Air 14 Electric	Body Dimensions 15	Pelican Stroke 16	Pelican Opening LxW 17							
Grain Drop Before Sampler (ft)	Grain Drop After Sampler (ft) 19	Access Safe 20 Yes No	Inspection Door OK? 21 Yes No							
Verified No Auxilliary Controls  22  Yes No	Location of Lockout OK?  Yes No	Lights OK for Exams? 24 Yes No								
Is Pelican Movement Steady?  25  Yes  No	Does Pressure Return Promptly? 26 Yes No	Air Pressure at Rest PSI 27								
Timer Make and Model	Grain Flow Rate Past Sampler	Calculated Timer Setting Seconds								
Secondary Make and Model	32	Delivery System Gravity  33 Pneumatic	Grams per Sample 34							
Total No. of Samples 35	Quantity Adjustment Sealed?	Delivery & Collection Box Secure?	Excess Returned to Lot?							
33	36 Yes No	37 Yes No	38 Yes No							
Dust Control Locations 39										
Weights: GIPSA Class X	GIPSA Class Y	Certified Other	40							
Number of Chinning Pines	Depth (ft)	<del>,                                      </del>	Procedures to Stop Breakage:							
41	42	Graded 43  Before or After Release	44							
Carrier I.D. by: 45										
Radio	Visual	Other								
Remarks/special restrictions when used to sample officially:										
46										
Olemature of Official Decreases			l neter							
Signature of Official Personnel:	Date: 48									

FORM FGIS 998 (05/25) Previous editions are obsolete. Expires 05/28

## **Instructions for Completing Questionaire**

- 1. Facility name, city, and state.
- 2. Name of FGIS field office.
- 3. Check the box indicating kind of elevator.
- 4. Storage capacity of elevator.
- Authorization Code-circle the numbers that apply to the intended sampler use.
- 6. Sampler Make & Model; e.g., Gamet 6800S.
- 7. Sampler Serial Number.
- 8. Is the sampler in a spout or on a belt end? For spout samplers-diameter or length x width cross sectional measurements or;
- 9. Belt Size-width and depth of grain carried.
- 10. General location of sampler; e.g., Headhouse 6th Floor; or Gallery.
- 11. Spout/belt name; e.g., Scale #1 lower garner.
- 12. Spout angle-90 is vertical. Belt Angle-0 is horizontal. Show normal angle and max/min limits of travel, if angle can be varied.
- 13. Belt speed-measure with belt loaded.
- 14. Check the box showing type of power.
- 15. Body dimensions for the sampler.
- Pelican stroke is the distance traveled from one side to the other.
- 17. Length and width of the pelican opening.
- 18. Distance in feet from release point.
- 19. Distance grain falls is used to estimate impact and breakage. For example, measure from sampler to bin bottom.
- 20. Is access to the sampler by approved ladder or stairs, and does the platform have an approved railing?
- 21. Are the inspection doors properly located on the sampler? Do they have appropriate seal hasps and hinges?
- 22. Check verified after you determine that the system controls have no bypasses, dump counters, timer interrupts, or programmable controllers.
- 23. Location of lockout ok-does the lockout provided meet FGIS requirements?
- 24. Light for examinations-can all exterior examination checks be made with lighting supplied?
- 25. For pneumatic/hydraulic samplers-is pressure sufficient to move the pelican across the stream of grain evenly, without lagging or slowing down.
- 26. For pneumatic/hydraulic samplers-pressure returns to maximum before next cut is initiated.
- 27. For pneumatic samplers-gauge pressure at rest. Maximum reached when no cuts are initiated.
- 28. Timer Make & Model; e.g., Eagle HP5 Model 9.
- 29. Flow past sampler should be figured out by timing a known amount, such as one scale draft, as it passes the sampler.
- 30. Calculate the timer setting in seconds based on grain flow rate past sampler. Also show whether this is based on a 200, 350, or 500 bushel sampling rate.
- 31. Secondary Sampler (divider) Make & Model; e.g., InterSystems MD300.
- 32. Secondary Sampler Serial Number.
- 33. Check box indicating type of sample delivery system.
- 34. Weight in grams received for the official sample.
- 35. Total number of samples needed for all interested parties.
- 36. Are the quantity adjustment features on secondary sampler fixed or sealed in place?
- 37. Is the sample delivery system secure from the air inlet to the collection box?
- 38. Is excess grain automatically returned from the secondary to the lot from which the sample was taken?
- 39. Location of dust collection ducts-are they located where they can affect the sample constituents? The measurements will serve as a record of approved duct work.
- 40. Weights-are weights official; i.e., supervised under the USGSA as Class X or Y-are weights Certified; i.e., supervised unofficially by a local organization-or are weights unofficial and not supervised, or not provided?
- 41. Shipping bins-number used.
- 42. Shipping bin depth(s).
- 43. Grading-will bin be held for grade or factor results before being released?
- 44. Procedures to stop breakage-will the bins require use of cushion level indicators, grain ladders, or baffles to reduce impact of grain and resulting breakage?
- 45. Carrier identification or stowage locations.
- 46. Special restrictions-any special procedural restrictions; e.g., weighback belt must be sealed, turnhead must be locked in position, cushion must be maintained in shipping bin, etc.
- 47. Name or signature of the official personnel who filled out the questionnaire.
- 48. Date information obtained.